







"LINEAR LED Lighting
LEDO 75-24L-T3
24 LED Single and DUO "

20725 NE. 16 AVE. #A-33 MIAMI, FLORIDA 33179

Tel: (305) 652-2599
Fax: (305) 650-8812
www.lumiron.com
Email: sales@lumiron.com





Benefits and Feature

- 1. Dimmable, DMX, Wi-Fi, RF Wireless.
- 2. Low Power Consumption.
- 3. Easy Installation and Low Maintenance.
- 4. Custom Lengths and Unique Color Sequencing Available.
- 5. Indoor and Outdoor.

Application

The new LEDO 75 18LED T3 Linear LED is a great product to improve the lighting experience for your future Cove and Architectural work, Jewelry Showcases, Museum Lighting, and Marine Lighting. The product contains 12 LED's with two colors that create an exceptional view for the eye.

Specifications

4 Inch - 48 Inch / 6 Inch - 10 ft *Custom Lengths Available Lengths Color Temperature Warm White / Neutral White / Cool White / Red / Amber / Green / Blue 4.5 Watts / 6 Watts (DUO) Wattage 436 lm / 581 lm (DUO) Lumens Input Voltage 12 or 24 VDC View Angle 120 degrees LED Spacing 0.6 Inch Center to Center / 0.5 Inch Center to Center (DUO) LED Type IP Rating Indoor Standard - Outdoor IP67 EPX Series Clear Acrylic Standard Lens Housing Anodized Clear Aluminum Extrusion * Custom Colors Available (e.g., Gold, Black) Mounting Wall Snap Mounting Standard/Swivel Mounting Brackets 2 Foot 18G 2 Cond Leads *Custom Wire lengths Available

Order Codes

SERIES	LENGTH	COLOR TEMP	#LED / F	VOLTAGE	IP LISTING	LENS	MOUNTING
LEDO 75	6" – 10'	CW Cool White NW neutral white WW warm white SCL single color LED	24L T3 6W/FT	12 or 24VDC	IN Indoor EPX Outdoor	CL clear MK Milky	WS wall snap SV swivel VR velcro MG magnet Custom Mounting

Order Examples

SERIES	LENGTH	COLOR TEMP	#LED / F	VOLTAGE	IP LISTING	LENS	MOUNTING
LEDO 75	4'6"	WW	24L T3	24 VDC	IN Indoor	CL clear	WS wall snap

Modeling

Isometric View



Top View







Transf. Excl.

IP 20

IP 67 EPX





12 or 24 VDC 12 LED PER/ft





