







"LINEAR LED Lighting
LEDO 75-24L-T3
24 LED Single and DUO "

20725 NE. 16 AVE. #A-33 MIAMI, FLORIDA 33179

Tel: (305) 652-2599
Fax: (305) 650-8812
www.lumiron.com
Email: sales@lumiron.com





Benefits and Feature

- 1. Dimmable, DMX, Wi-Fi, RF Wireless.
- 2. Low Power Consumption.
- 3. Easy Installation and Low Maintenance.
- 4. Custom Lengths and Unique Color Sequencing Available.
- 5. Indoor and Outdoor.

Application

The new LEDO 75 24LED T3 Linear LED is a great product to improve the lighting experience for your future Cove and Architectural work, Jewelry Showcases, Museum Lighting, and Marine Lighting. The product contains 24 LED's with two colors that create an exceptional view for the eye.

Specifications

Lengths

4 Inch - 48 Inch / 6 Inch - 10 ft

*Custom Lengths Available

Color Temperature

Warm White / Neutral White / Cool White / Red / Amber / Green / Blue

Wattage

4.5 Watts / 6 Watts (DUO)

Lumens

436 lm / 581 lm (DUO)

Input Voltage

12 or 24 VDC

View Angle

120 degrees

LED Spacing

LED Type

0.6 Inch Center to Center / 0.5 Inch Center to Center (DUO)

IP Rating

T3

Indoor Standard - Outdoor IP67 EPX Series

Lens

Clear Acrylic Standard

Housing

Anodized Clear Aluminum Extrusion * Custom Colors Available (e.g., Gold, Black)

Mounting

Wall Snap Mounting Standard/Swivel Mounting Brackets

Leads

2 Foot 18G 2 Cond

*Custom Wire lengths Available

Order Codes

SERIES	LENGTH	COLOR TEMP	#LED/F	VOLTAGE	IP LISTING	LENS	MOUNTING
LEDO 75	6" – 10'	CW Cool White NW neutral white WW warm white SCL single color LED	24L T3 6W/FT	12 or 24VDC	IN Indoor EPX Outdoor	CL clear MK Milky	WS wall snap SV swivel VR velcro MG magnet Custom Mounting

Order Examples

SERIES	LENGTH	COLOR TEMP	#LED / F	VOLTAGE	IP LISTING	LENS	MOUNTING
LEDO 75	4'6"	WW	24L T3	24 VDC	IN Indoor	CL clear	WS wall snap

Modeling

Isometric View



Top View







Transf. Excl.

IP 20

IP 67 EPX





12 or 24 VDC 12 LED PER/ft





