

IFDR.E363518 - LOW-VOLTAGE LIGHTING SYSTEMS, POWER UNITS, LUMINAIRES AND FITTINGS

Low-voltage Lighting Systems, Power Units, Luminaires and Fittings

See General Information for Low-voltage Lighting Systems, Power Units, Luminaires and Fittings

LUMIRON INC

E363518

20725 Ne 16Th Ave Ste A33

Miami, FL 33179-2126 USA

Low voltage LED luminaire, located in Class 2 circuitry, Model(s) *LUMIRTAPE A - B - C - D - E - F - G TPL - 16250 - 300 - CW - 12V - T3 - EPX (^)*

(^) - A = LUMIRTAPE TAPE LIGHT : TPL, B = LENGTH OF THE TAPE in feet: 16250 stands for the length in feet, which is 16.25ft, which equals to 4.95 meters. The minimum length of tape of LED is 0.1 meters, the maximum is 50 meters. The same for all models, C = NUMBER OF LED's, D = COLOR LED : Red, Green, Blue, Amber, CW - Pure White, NW -Neutral White, WW - Warm White, RGB, RGBW, RGB-CW, RGB - NW , RGB - WW, E = VOLTAGE: 5-24Vdc, F = TYPE OF LED T2: 2835 T3: 5060 T4: 3528 T5: 4008, G = EPX: WATERPROOF, IND: NON WATERPROOF.

Last Updated on 2018-10-25

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"